

**THE NEXT
GENERATION**
15 JAHRE GARANTIE*

check-floors.com

CHECK ✓
one

product information

guarantee	15 years*
wear layer	0.55 mm
Clicksystem	Innovation-Click
Groove	bevelled edge
Sealing	UV coating

dimensions and packing

dimension		1220 x 229 x 5 mm
packaging unit (PU)	CHECK one Wide plank incl.	8 planks = 2.235 sqm
pallet size	Underlay	48 PU = 107.282 sqm
utilisation class		42
dimension		592 x 148 x 5.5 mm
packaging unit (PU)	CHECK one Herringbone incl.	20 planks = 1.752 sqm
pallet size	Underlay	60 PU = 105.139 sqm
utilisation class		42

technical specifications/ accomplished inspections:

Lightfast	ISO 105-BO2	≥ 6
Stain resistance	EN 438-2	✓
Dimensional stability	ASTM F2199-20	✓
Fire behaviour	EN 13501-1	Bfl, s1
Residual indentation	ASTM F1918-18, F3261-17	0.07 mm
Sliding resistance	EN 14041	DS
Thermal resistance	EN 12664	0.045 (m ² K)/W
Floor heating	EN 12664	suitable for hot water, max 27 degrees
Formaldehyde class	EN 717-1	E1
Impact Sound Improvement	ISO 10140-3 / ISO 717-2	21 dB

* according to guarantee conditions

All given values are recommended values.
Product-related fluctuations can not be excluded.



Scheuten-Solar-Str. 2 • 45881 Gelsenkirchen • Tel.: +49 209 / 59034-0 • Fax: +49 209 / 59034-29

E-Mail: info@koczwaravertrieb.de • Web: www.koczwaravertrieb.de, check-floors.com