

FACTS



		PREMIUM WOOD	PREMIUM HERRINGBONE	PREMIUM STONE
Use Class		33	33	33
Thickness	EN 17539	6 mm (5+1 mm)	6 mm (5+1 mm)	6 mm (5+1 mm)
Width	EN 17539	225 mm	146 mm	457 mm
Length	EN 17539	1522 mm	730 mm	914 mm
Panels per Box		5	16	4
Box Content		1.712 m²	1.705 m²	1.671 m²
Box Weight		17.95 kg	17.88 kg	17.53 kg
Profile		2G™ Angling Installation System	UNIZIP® One Panel System	2G™ Angling Installation System
Bevel		Microbevel 4-sided	Microbevel 4-sided	Microbevel 4-sided
Wearlayer	ISO 24340:2006 (E)	0.55 mm	0.55 mm	0.55 mm
Surface		EiR/Synchronpore Supermatt (Gloss level 3-5)	EiR/Synchronpore (Gloss level 3-5)	EiR/Synchronpore Supermatt (Gloss level 3-5)
Reaction to Fire (CE)	EN 13501-1	B1	B1	B1
Thermal Conductivity	EN 12667	0.111 W/m·K	0.111 W/m·K	0.111 W/m·K
Underfloor Heating Suitability		✓	✓	✓
Slip Resitance		R9	R9	R9
Abrasion Resistance		≥ 5,000 r	≥ 5,000 r	≥ 5,000 r
Locking Strenght	ISO 24334	≥ 3.5 kN/m	≥ 3.5 kN/m	≥ 3.5 kN/m
Microscratch Resistance	EN 16094	B2	B2	B2
Dimensional Stability	EN ISO 23999	≤ 0.15 %	≤ 0.15 %	≤ 0.15 %
Impact Sound Insulation		1 mm IXPE, 10X	1 mm IXPE, 10X	1 mm IXPE, 10X
Impact Sound Improvement	ISO 10140-3	20 dB	20 dB	20 dB
Formaldehyde/VOC Emissions Free		✓	✓	✓
Phthalat Free		✓	✓	✓