

**THE NEXT
GENERATION**
15 JAHRE GARANTIE*

check-floors.com

CHECK ✓
one

product information

| | |
|-------------|------------------|
| guarantee | 15 years* |
| wear layer | 0.55 mm |
| Clicksystem | Innovation-Click |
| Groove | bevelled edge |
| Sealing | UV coating |

dimensions and packing

| | | |
|---------------------|-----------------------------|-----------------------|
| dimension | | 1220 x 229 x 5 mm |
| packaging unit (PU) | CHECK one Wide plank incl. | 8 planks = 2.235 sqm |
| pallet size | Underlay | 48 PU = 107.282 sqm |
| utilisation class | | 42 |
| dimension | | 592 x 148 x 5.5 mm |
| packaging unit (PU) | CHECK one Herringbone incl. | 20 planks = 1.752 sqm |
| pallet size | Underlay | 60 PU = 105.139 sqm |
| utilisation class | | 42 |

technical specifications/ accomplished inspections:

| | | |
|--------------------------|-------------------------|--|
| Lightfast | ISO 105-BO2 | ≥ 6 |
| Stain resistance | EN 438-2 | ✓ |
| Dimensional stability | ASTM F2199-20 | ✓ |
| Fire behaviour | EN 13501-1 | Bfl, s1 |
| Residual indentation | ASTM F1918-18, F3261-17 | 0.07 mm |
| Sliding resistance | EN 14041 | DS |
| Thermal resistance | EN 12664 | 0.045 (m ² K)/W |
| Floor heating | EN 12664 | suitable for hot water, max 27 degrees |
| Formaldehyde class | EN 717-1 | E1 |
| Impact Sound Improvement | ISO 10140-3 / ISO 717-2 | 21 dB |

* according to guarantee conditions

All given values are recommended values.
Product-related fluctuations can not be excluded.



Scheuten-Solar-Str. 2 • 45881 Gelsenkirchen • Tel.: +49 209 / 59034-0 • Fax: +49 209 / 59034-29

E-Mail: info@koczwaravertrieb.de • Web: www.koczwaravertrieb.de, check-floors.com