



Plank 4052, 4118, 4119

Product information

Clicksystem	Loc-Click
Chamfer	bevelled edge
Sealing	UV varnish
Wear layer	0.2 mm
Utilisation class	31

Technical data

Dimension	1220 x 182 x 3.2 mm
Packing unit (PU)	14 Planks = 3.109 sqm
Pallet size	44 PU = 136.78 sqm

Test results

Lightfast	ISO 105-B02	≥ 6
Dimensional stability	ISO 23999	✓
Fire behavior	EN 13501-1	Bfl, s1
Residual indentation	ISO 24342	0.01 mm
Slip resistance	EN 13893, EN 14041	DS
Anti-Slip property	DIN 51130	R10
Thermal Resistance	EN 14041	0.039 m ² K/W
Underfloor heating	EN 12667	Suitable for hot water, max 27 degrees
Formaldehyde class	EN 717-1	E1
Chair caster suitability	ISO 4918	no damage

All specified values are standard values.
Production-related fluctuations can not be ruled out.



Scheuten-Solar-Str. 2 • 45881 Gelsenkirchen • Tel.: +49 209 / 59034-0 • Fax: +49 209 / 59034-29

E-Mail: info@koczwaravertrieb.de • Web: www.koczwaravertrieb.de